

ATT 1190



















100 METRIC TONNES



OUTRIGGERS FULLY EXTENDED OVER 360 DEGREES (Width 7.60m)



On stable surface, wheels lifted from the ground, fully levelled. Axles locked.

EXTENDING FROM 12m TO 36,75m - 16 TON COUNTERWEIGHT (Tyres 20.5x25 or 16.00x25)																
 *  R (m)	T2=0% T3=0% T4=0% T5=0%	T2=47% T3=0% T4=0% T5=0%	T2=93% T3=0% T4=0% T5=0%	T2=93% T3=47% T4=0% T5=0%	T2=93% T3=93% T4=0% T5=0%	T2=93% T3=93% T4=47% T5=0%	T2=93% T3=93% T4=93% T5=0%	T2=100% T3=100% T4=100% T5=0%								
	12,00 m / (11)*		15,83 m / (8)*		19,58 m / (8)*		23,48 m / (6)*		27,30 m / (6)*		31,20 m / (5)*		35,02 m / (4)*		36,75 m / (3)*	
																
	Max. 76°	80.00	Max. 76°	60.00	Max. 79°	60.00	Max. 80.5°	38.00	Max. 80.5°	39.80	Max. 80.5°	33.65	Max. 80.5°	25.50	Max. 80.5°	22.15
3.0	68.20	80.00	73.90	60.00	77.50	60.00										
3.5	65.50	71.75	72.00	60.00	76.00	60.00	78.50	38.40								
4.0	62.80	66.40	70.10	60.00	74.50	58.25	77.30	38.80	79.50	40.20						
4.5	59.90	61.80	68.10	58.35	73.00	54.05	76.10	39.30	78.50	40.80						
5.0	57.00	57.70	66.10	54.45	71.40	50.60	74.90	39.90	77.50	40.50	79.40	33.65				
6.0	50.70	50.00	61.90	48.00	68.20	44.20	72.30	37.65	75.40	35.70	77.60	31.20	79.20	25.50		
7.0	43.60	42.80	57.60	41.30	65.00	39.00	69.70	33.55	73.20	31.85	75.70	28.65	77.70	25.50	78.30	22.15
8.0	35.20	36.55	52.90	35.15	61.50	34.30	67.00	29.90	70.90	28.35	73.80	26.30	76.10	24.10	76.80	20.95
9.0	23.80	31.70	47.90	30.35	58.00	29.55	64.30	27.15	68.60	25.80	71.90	24.15	74.40	22.35	75.20	19.85
10.0			42.40	26.55	54.30	25.80	61.50	24.70	66.30	23.45	69.90	21.95	72.70	20.95	73.60	18.20
11.0			36.20	23.45	50.30	22.65	58.50	22.45	63.90	21.30	67.90	20.15	71.00	19.40	71.90	16.55
12.0			28.60	20.10	46.20	19.30	55.40	19.60	61.40	19.55	65.80	18.50	69.20	18.00	70.30	15.20
13.0			17.70	17.45	41.60	16.65	52.20	16.95	58.80	17.10	63.60	17.00	67.40	16.85	68.50	13.95
14.0					36.60	14.50	48.80	14.75	56.20	14.90	61.40	15.50	65.40	15.65	66.80	12.80
15.0					30.80	12.70	45.30	12.95	53.40	13.10	59.20	13.60	63.50	14.00	65.10	11.85
16.0					23.60	11.10	41.50	11.35	50.60	11.55	56.90	12.05	61.50	12.45	63.20	11.00
17.0					11.80	9.70	37.40	9.95	47.70	10.10	54.50	10.70	59.50	11.10	61.30	10.20
18.0							32.80	8.75	44.60	8.95	52.10	9.45	57.50	9.85	59.40	9.45
19.0							27.40	7.75	41.30	7.95	49.60	8.40	55.40	8.80	57.50	8.80
20.0							20.60	6.85	37.80	7.00	47.00	7.50	53.20	7.90	55.50	7.80
21.0							8.50	6.05	33.90	6.15	44.30	6.70	51.00	7.05	53.50	7.00
22.0									29.50	5.50	41.40	5.95	48.80	6.35	51.40	6.30
23.0									24.40	4.85	38.30	5.30	46.40	5.65	49.20	5.65
24.0									17.70	4.25	35.00	4.70	43.90	5.05	47.00	5.05
25.0											31.30	4.20	41.40	4.50	44.70	4.50
26.0											27.20	3.70	38.60	4.05	42.30	4.05
27.0											22.30	3.25	35.70	3.60	39.70	3.60
28.0											15.80	2.90	32.60	3.20	37.00	3.20
29.0													29.00	2.80	34.10	2.80
30.0													25.10	2.50	30.90	2.50
31.0													20.00	2.15	27.20	2.15
32.0													13.60	1.85	23.40	1.85
33.0															18.40	1.60
34.0															10.80	1.30
Af tot α = 0°	0°	13.05	0°	7.30	0°	3.80	0°	1.95	0°	0.70						
maxi α = 0° zonder last	12,00 m		15,83 m		19,58 m		23,48 m		27,30 m		27,30 m		27,30 m		27,30 m	

 UNAUTHORISED RANGE, LOADED OR WITHOUT LOAD

